



Fiberglass Pipe Section :

Fiber glass pipe sections are designed for easy and rapid installation. One piece molded insulation made from glass fiber bonded with high temperature resistant binder. Fiber glass pipe sections are non combustible and shot free. Pipe diameter from 20 mm to 300 mm is available.

Fiber Glass pipe sections are also available with

Aluminum Foil facing.

Characteristics :

Densities in (Kg/M3)	80
Thickness in (mm)	25, 50
Dimensions :	0.900 mm
TEMPERATURE RANGE	U p to 230°C
Chemical Stability	Chemically inert, rot Proof and odorless
Fire Safety	Non Combustible
Biological	Resistant to fungus, bacteria and vermin
Thermal Conductivity	0.030 W/mk at 25 Deg C
Corrosion Resistance	Non corrosive to metal

Application :

Fiber Glass Pipe section are used for thermal and acoustic Insulation of :

- Heating and hot water Pipe
- Steam Pipe up to 230 Deg C
- Chilled Water Pipe and cold water service Pipes



SHETH INSULATIONS PVT. LTD.

Dealers & Contractor in Thermal Insulation & Waterproofing Materials

Your Energy Saving Partner

Advantages :

- Green Building material: Low nourish energy
- Zero Ozone Depleting Potential
- Non Combustible, Does not emit toxic fumes
- Low thermal conductivity , cost effective, Excellent thermal resistance
- Non Corrosive to metal
- No shot content and Impurities
- Non Hygroscopic
- Resistant to Chemical, oil, fungus, bacteria, vermin and rot attack