



SHETH INSULATIONS PVT. LTD.

Dealers & Contractor in Thermal Insulation & Waterproofing Materials

Your Energy Saving Partner



FEVICOL SR 505 :

Multipurpose Mild Smell Synthetic Rubber Adhesive.

FEVICOL SR 505 is a synthetic rubber based adhesive. Widely used in many application HVAC DUCTS, Chilled water pipe line, under deck insulation, industrial and residential projects. Easy to apply and having mild odor.

Characteristics :

Appearance	Light yellow liquid
Viscosity at 30° ±	12 -16 Poise
Temperature Resistance	-20° C to 80°C
Specific Gravity	0.82 – 0.86
Coverage by Spreader	6-6.5 m ² / Kg (Bonded area)
(Under identical lab test conditions at ambient, on smooth nonporous substrate with single side application)	
Shelf Life & Storage	18 months from the date of manufacturing & when stored in a dry and cool place in the original unopened container (Recommended Storage temperature: 20-30°C)
Packing	25 Kg Plastic Drum.

Application :

- HVAC DUCTING: To bond Nitrile Rubber / EPDM/ XLPE (20 mm thickness max), Glass wool/ Rockwool. Puff to Duct Surface.
- Chilled water piping – To bond Nitrile Rubber/ EPDM/ XLPE (30 mm thickness Max.) Glass Wool, Rock wool, PUF to MS Pipe Line.
- Acoustic Insulation – To bond Nitrile Rubber to concrete walls, vertical surface & Duct lining.
- Wall Paneling – To bond Nitrile Rubber / EPDM/ XLPE (20 mm Thickness Max.) Glass Wool/ Rockwool to smooth Concrete wall surface.
- Under deck Insulation- To bond Nitrile Rubber/EPDM/ XLPE (20 mm Thickness max). Glass wool /Rockwool, PUF to smooth concrete wall surface (Mechanical fasteners are recommended for under deck insulation)

Admn. Off. Plot No. 402/B, GIDC PHASE II, Opp. Water Tank, Vatva, Ahmedabad -382445

Tele Fax : +91(079) 25892644, 2583 3473,40083341, Email: info@shethinsulations.com, sales@shethinsulations.com

Website : www.shethinsulations.com, www.shethinsulations.in



SHETH INSULATIONS PVT. LTD.

Dealers & Contractor in Thermal Insulation & Waterproofing Materials

Your Energy Saving Partner

Advantages :

- Excellent Adhesion to multiple substrates.
- Very mild smell ensures the applicators and users not be harmed
- Strong bond durability. (Aging Resistance)
- Free from carcinogenic compound.

Precautions & Limitations

- Keep the container closed when not in use. Stir the Adhesive well before use.
- Contains flammable solvents, so precautions required in storing.
- Adhesive or vapor from the adhesive should not come in contact with fire spots, naked flames or welding area on shop floor/work site.
- Do not use adhesive on undulated surface
- Use of PPE's (protective hand gloves, mask and goggles) is strongly recommended
- MSDS available on request.

NOTE: The Product information & application details given by the company & its agents has been provided in good faith and meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and on-site workmanship are factors beyond our control, there are no expresses or implied guarantee/ warranty as to the results obtained. The company does not assume any liability or any consequential damage for unsatisfactory results, arising from the use of our products.

Admn. Off. Plot No. 402/B, GIDC PHASE II, Opp. Water Tank, Vatva, Ahmedabad -382445

Tele Fax : +91(079) 25892644, 2583 3473,40083341, Email: info@shethinsulations.com, sales@shethinsulations.com

Website : www.shethinsulations.com, www.shethinsulations.in